


LGH Lead Assemblies and Receptacles, 30 KVDC, LGH 2 (Continued)

RFI Shielded Double End Lead Assemblies*



Assembly Length	Part Number
12.0	867448-1
304.8	
24.0	867448-2
609.6	
36.0	867448-3
914.4	
48.0	867448-4
1219.2	


Note: Standard length leads are tabulated here. Tyco Electronics can make available numerous variations in length and material to suit almost any application. Choices of insulation materials include TEFLON, UL listed silicone and UL listed PVC. Other materials, colors, wire and configurations can be used in manufacture. For more information, consult Tyco Electronics.

* These RFI Shielded Lead Assemblies mate with receptacle 861256-1.

Glass-Epoxy Receptacles with 1.44 [36.58] Barrel Depth

Flanged, for Hermetic Seal
Part Number 861256-1


Weight — 20 grams



These receptacles are for use with RFI Shielded Leads shown on the preceding page.


With Recessed Terminal for Encapsulated Units
Part Number 849588-1

Weight — 20 grams



Flanged, Bolt Mount
Part Number 850910-1


Weight — 42 grams



Note: If the panel or mounting hardware is at ground potential, guard against arc-over and breakdown within the area defined by this line.


Bolt-mount, Feed-through
Part Number 850735-1

Weight — 70 grams




For Encapsulated Units
Part Number 1-849587-1

Weight — 17 grams



Splice
Part Number 850555-1

Weight — 43 grams



Receptacles are available with gold plated contacts.