



Terminals and Splices

↳ Quick Disconnect Receptacles - Insulated

AMP 8-640911-1 Active

**Directive 2002/95/EC
Compliant**

RoHS Compliant

(Tyco Electronics P/N: 8-640911-1)

Searchable Features:	
Brand:	AMP
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Processes:	Not relevant for lead free process
Proprietary Name:	PIDG FASTON
Receptacle Style:	Straight
Fully Insulated:	No
Wire Range (mm [AWG]):	22-18
Tab Fit (mm [in]):	5.21 x 0.81 [.205 x .032]
Insulation Support:	Insulation Support
Insulation Diameter (mm [in]):	3.43 [.135] Max.
Insertion Force:	Normal

Other Properties:	
RoHS/ELV Compliance History:	Always was RoHS compliant
Voltage (VAC):	300
RU (UL Component Program):	Approved
CSA Certified:	Yes
Color:	Red
Wire Range (CMA):	509 – 1,900
Insulation Material:	Nylon
Stock Thickness (mm [in]):	0.41 [0.016]
Packaging Quantity:	100/Box

Material:	Brass
Finish:	Tin
Dimple Type:	Dimple with wire stop
Packaging Method:	Loose Piece

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)
