



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED	12/1/93	<i>RAC</i>

NOTES:
1. CAPTURED CENTER CONTACT

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions <u>MIL-STD-348</u>	Temperature Rating <u>-65°C To +165°C</u>
Frequency Range (GHz) <u>DC - 18</u>	<u>FIG 310.2</u>	Vibration - MIL-STD-202, Method 204, Condition D, 20G's
Volt Rating (VRMS MAX) <u>N/A</u>	Recommended Mating Torque <u>7-10 InLbs</u>	Shock - MIL-STD-202, Method 107, Condition B
VSWR <u>1.04±.006 F(GHz)</u>	Mating Characteristics:	Thermal shock MIL-STD-202, Method 107, Condition B
Insertion Loss (dB MAX) <u>.04 √F(GHz)</u>	Insertion (MAX Lbs) <u>3.0</u>	Except High Temp <u>115°C</u>
RF Leakage (dB MIN) <u>-70 - F(GHz)</u>	Withdrawal (MIN Oz) <u>1.0</u>	Moisture Resistance - MIL-STD-202, Method 106
Corona, 70,000 Ft (VRMS MIN) <u>333</u>	Force To Engage (In/Lbs MAX) <u>2.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Dielectric Withstanding Voltage (VRMS MIN) <u>1000 @ sea level</u>	Force To Disengage (In/Lbs MAX) <u>2.0</u>	
Contact Resistance (Milliohms MAX)	Center Contact Captivation	
Center Contact <u>2.0</u>	Axial <u>6.0 Lbs</u>	
Outer Contact <u>2.0</u>	Radial <u>N/A</u>	
RF High Potential (VRMS MIN @ 5 MHz) <u>667 @ sea level</u>	Weight (Grams) <u>T.B.D.</u>	
I.R.(Megohms) <u>5000</u>		

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER NICKEL PER QQ-N-290
GASKET	CONDUCTIVE ELASTOMETERS PER MIL-G-83528	N/A

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY <i>RAC</i> DATE 12/1/93	AMP Incorporated
FRAC. DEC. ANGLES	CHECKED BY <i>RAC</i>	140 Fourth Avenue
± 1/64 ± .005 ± °	APPD BY <i>RAC</i> DATE 12/1/93	Waltham, MA 02451-7599
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	AMP
	NO. AP. <u>N/A</u>	TITLE OSM TWO HOLE FLANGE MOUNT JACK RECEPTACLE WITH EMI/RFI GASKET
		SIZE B CODE IDENT NO. 26805 2052-3354-02 REV 01 ₀
		SCALE 5:1 SHEET 1 OF 1