

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION AUG ,2005.




© COPYRIGHT 2005 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
E	B	P	LTR	DESCRIPTION	DATE	DWN	APVD
		B		ECR-07-018334	07/08/07	AM	FWK

NOTES:

- ELECTRICAL DATA: CONTACT RESISTANCE: 10 mOhm MAX
INSULATION RESISTANCE: 100 MOhm MIN at 500VDC
CURRENT RATING: 5 AMPS
BREAKDOWN VOLTAGE: 500 VAC MIN PER MINUTE
- ENVIRONMENTAL: OPERATING TEMPERATURE: -25°C TO +90°C
SEALING REQUIREMENTS: IP67
- PROD SPEC: 108-3641
- PACKAGING: 107-3334
- FOR TECHNICAL DATA REFER TO YOUR LOCAL TYCO ELECTRONICS SALES OFFICE
- ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED

ITEM	DESCRIPTION	MATERIAL	FINISH/COLOUR	QTY
1	SCREW NUT	BRASS	NICKEL PLATED	1
2	CONNECTOR BODY	POLYURETHANE	BLACK	1
3	SOCKET CONTACT	BRASS	0.15µm GOLD PLATED OVER NICKEL	3
4	3 CORE CABLE (CORES 22AWG TO UL2464)	PVC JACKET UV RESISTANT	BLACK	1
5	'O' RING	VITON	GREEN	1



10000	500 mm	M8 STRAIGHT FEMALE CONNECTOR 10.0m CABLE	1814434-5	OBSOLETE
7000	350 mm	M8 STRAIGHT FEMALE CONNECTOR 7.0m CABLE	1814434-4	OBSOLETE
5000	250 mm	M8 STRAIGHT FEMALE CONNECTOR 5.0m CABLE	1814434-3	ACTIVE
3000	150 mm	M8 STRAIGHT FEMALE CONNECTOR 3.0m CABLE	1814434-2	OBSOLETE
2000	100 mm	M8 STRAIGHT FEMALE CONNECTOR 2.0m CABLE	1814434-1	OBSOLETE
DIM A	TOL 'B'	DESCRIPTION	PART NUMBER	PART STATUS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN H M RAGHAVENDRA 23AUG05	Tyco Electronics Corporation Bideford, UK, EX39 4HE	
DIMENSIONS: mm		CHK F.WHEELER-KING 15DEC05	NAME M8 STRAIGHT FEMALE CONNECTOR 3 POSITION, PVC CABLE	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD F.WHEELER-KING 15DEC05	SIZE A3	CAGE CODE 00779
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC -	DRAWING NO C-1814434	RESTRICTED TO -
MATERIAL -		FINISH -	WEIGHT -	SCALE NTS
CUSTOMER DRAWING			SHEET 1 OF 1	REV B