

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AF	50	K1	ECR-13-017177	05NOV13	PKS RRP

1 CONTINUOUS STRIP ON REELS WITH TERMINALS LOCATED ON 5.08[.200] CENTERS.  
 2 SLOT ACCEPTS A 0.25-0.32 mm DIA [#30-#28] AWG COPPER MAGNET WIRE ONLY (2 WIRES MAX).  
 3 WIRE BARREL ACCEPTS 0.12-0.40 mm<sup>2</sup> [#26-#22] AWG LEAD WIRE.  
 4 IDENTIFICATION NUMBER FOR MAGNET WIRE RANGE.

SECTION A-A  
 ROTATED 90° CW

STRIP LENGTH ±.015	TYPE	WIDTH	HEIGHT ±.002	WIRE
3.56 [.140]	F	1.40 [.055]	0.97 [.038] 0.35 [.22]	
			0.89 [.035] 0.20 [.24]	
			0.86 [.034] 0.14 [.26]	

WIRE BARREL CRIMP

REVERSE REEL OF 62608-1	TIN PLATE PER MIL-T-10727	62608-3
-	TIN PLATE PER MIL-T-10727	62608-1
REELING	FINISH	PART NO.
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DK SCHRUM 8/3/89
DIMENSIONS: INCHES		CHK MS FEHER 8/16/89
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD N.E. NEFF 8/16/89
0 PLC ± -		NAME
1 PLC ± -		TE Connectivity
2 PLC ± -		PRODUCT SPEC
3 PLC ± 0.38[.015]		APPLICATION SPEC
4 PLC ± -		114-2069
ANGLES ± -		WEIGHT -
MATERIAL BRASS	FINISH SEE TABLE	SIZE A2 CAGE CODE 00779
CUSTOMER DRAWING		DRAWING NO C=62608
SCALE 8:1		SHEET 1 of 1
REV K1		RESTRICTED TO -

1471-9 (3/11)

62608

B

A