



PCB CONFIGURATION

- 1 ZINC PER QQ-Z-363
- 2 BERYLLIUM COPPER PER ASTM-B-196
- 3 PTFE PER MIL-P-19468
- 4 GOLD PLATE PER MIL-G-45204 0.76µm [000030] MINIMUM THICK.
- 5 TIN PLATE PER ASTM-B-545, 3.04µm [000120] MINIMUM THICK.
- 6. SEE INSTRUCTION SHEET 408-9889.
- 7 NICKEL PLATE PER QQ-N-290 5.08 µm [000200] MINIMUM THICK.
- 8 PACKAGE: 100 PER BAG/CARTON
- 9 PACKAGE: 28 PER TRAY PACKAGE

REVISIONS				
P	CLR	DESCRIPTION	DATE	BY
A1		REVISED PER ECR-17-009300	27JUN2017	LN RS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	VERSION
APPROVED: J. HAVENER		DATE	VERSION
DRAWN: J. HAVENER		DATE	VERSION
CHECKED: J. HAVENER		DATE	VERSION
DIMENSIONS: OTHER DIMENSIONS: DIMENSIONS: DIMENSIONS:		OTHER DIMENSIONS: DIMENSIONS: DIMENSIONS: DIMENSIONS:	
NOTES: OTHER DIMENSIONS: DIMENSIONS: DIMENSIONS:		OTHER DIMENSIONS: DIMENSIONS: DIMENSIONS: DIMENSIONS:	
MATERIAL: SEE NOTES 1 - 3		MATERIAL: SEE NOTES 1 - 3	
WEIGHT: 0.000000		WEIGHT: 0.000000	
CUSTOMER DRAWING		CUSTOMER DRAWING	
PART NUMBER		PART NUMBER	
SHELL FINISH		SHELL FINISH	
TE Connectivity		TE Connectivity	
JACK, VERTICAL, PCB, 75 OHM, COMMERCIAL BNC		JACK, VERTICAL, PCB, 75 OHM, COMMERCIAL BNC	
SIZE: A2		SIZE: A2	
CODE: 00779		CODE: 00779	
DRAWING NO: 6274291		DRAWING NO: 6274291	
SCALE: 5:1		SCALE: 5:1	
SHEET: 1		SHEET: 1	
REV: A1		REV: A1	

6274291