

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	ECR-15-018270	07DEC2015	DW	CW
	B1	ECR-18-013580	30AUG2018	WQR	CW
	B2	ECR-19-000492	23JAN2019	AL	CW
	C	ECR-19-004179	24APR2019	AL	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:
 INSULATION MATERIAL: PC
 RATED VOLTAGE: 50V
 RATED CURRENT: 5A
 INSULATION RESISTANCE: $\geq 400M\Omega$
 RATED IMPULSE VOLTAGE: 0.8KV
 POLLUTION DEGREE: 3
 FLAMMABILITY: UL94V-0
 MATING CYCLES: 500 CYCLES
 WIRE RANGE: 0.08~0.52 mm² (28~20 AWG)
 CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.
 (ORDER No. REFER TO DRAWING:T20700X20XX000)

注释:

1. 技术参数:
 绝缘材料: PC
 额定电压: 50V
 额定电流: 5A
 绝缘电阻: $\geq 400M\Omega$
 额定脉冲电压: 0.8KV
 污染等级: 3
 阻燃等级: UL94V-0
 插拔次数: 500次
 接线范围: 0.08~0.52 mm² (28~20 AWG)
 接线类型: 冷压接

2. 端子需要单独订购.
 (订货号参考图面: T20700X20XX000)

T2111092201-000	HMN-009-F	HMN-009 FEMALE MODULE INSERT HMN-009模块母插
PART NUMBER 料号	DESCRIPTION 描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC ±-
	1 PLC ±-
	2 PLC ±-
	3 PLC ±-
	4 PLC ±-
	ANGLES ±-
MATERIAL	FINISH
-	-
-	-

DWN	24MAR2015
David Wang	
CHK	24MAR2015
Chris Wang	
APVD	24MAR2015
Xiang Xu	
PRODUCT SPEC	108-137064
APPLICATION SPEC	114-137064
WEIGHT	-
Customer Drawing	

TE Connectivity		NAME		RESTRICTED TO
		HMN-009-F		
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
A3	00779	©-T2111092201000	-	
SCALE		SHEET	OF	REV
3:2		1	1	C

1470-19 (3/13)