

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	16APR2015	DL	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 INSULATION MATERIAL: PC  
 RATED VOLTAGE: 50V  
 RATED CURRENT: 1A  
 INSULATION RESISTANCE:  $\geq 400M\Omega$   
 RATED IMPULSE VOLTAGE: 0.8KV  
 POLLUTION DEGREE: 3  
 FLAMMABILITY: UL94V-0  
 MATING CYCLES: 1500  
 OPERATION TEMPERATURE:  $-40^{\circ}C \sim +70^{\circ}C$

注释:

1. 技术参数:  
 绝缘材料: PC  
 额定电压: 50V  
 额定电流: 1A  
 绝缘电阻:  $\geq 400M\Omega$   
 脉冲电压: 0.8KV  
 污染等级: 3  
 阻燃等级: UL94V-0  
 插拔次数: 1500  
 工作温度:  $-40^{\circ}C \sim +70^{\circ}C$

HMN-USB-M	T2114000101-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC $\pm$
	1 PLC $\pm$
	2 PLC $\pm$
	3 PLC $\pm$
	4 PLC $\pm$
	ANGLES $\pm$
MATERIAL	FINISH
-	-
-	-

DWN	16APR2015
DAVID LI	
CHK	16APR2015
CHRIS WANG	
APVD	16APR2015
XU XIANG	
PRODUCT SPEC	108-137066
APPLICATION SPEC	114-137066
WEIGHT	-
CUSTOMER DRAWING	

TE Connectivity		NAME	
		HMN-USB-M	
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	-	©-T2114000101000	-
SCALE		SHEET	REV
2:1		1 OF 1	A

1470-19 (3/13)