

ATUM-24/6-0-STK Product Details



ATUM-24/6-0-STK

TE Internal Number: 4177512003



Heat Shrink Tubing

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Heat Shrinkable Tubing
- Product Name = ATUM
- Product Source = U.K., U.S.
- Semiflexible
- Thin Wall Style

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [RAYCHEM_TUBING_CATALOG_SECT1_PRODUCTS_A-H](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- **Product Type** = Heat Shrinkable Tubing
- Color = Black

Electrical Characteristics:

- **Recovered ID, Max.** (mm [in]) = 6.00 [0.236]

Dimensions:

- **Expanded ID, Min.** (mm [in]) = 24.00 [0.945]
- **Cut Length** (mm [in]) = 1220.00 [48.068]

Body Features:

- **Product Name** = ATUM
- **Pliancy** = Semiflexible
- **Wall Style** = Thin
- **Wall Type** = Dual
- **Lining Type** = Adhesive
- **Material** = Crosslinked Polyolefin
- **Shrink Ratio** = 4:1
- **Fluid Type** = Aviation Fuel, Brake Fluid, Chemicals/Solvents, Hydraulic Fluid, Lubricating Oil, Water
- **Resistant To** = Fluids, Mechanical Damage, Strain
- **Wall Thickness - Full Recovery (Nominal)** (mm [in]) = 2.25 [0.088]

Housing Features:

- **Material Systems** = No

Industry Standards:

- **Government/Industry Qualification** = No
- **Flammability Rating Type** = Flame-Retardant
- **UL Rating** = Recognized
- **CSA Certified** = No
- **Approved Standards** = UL E85381
- **RoHS/ELV Compliance** = RoHS compliant, ELV compliant
- **Lead Free Solder Processes** = Not relevant for lead free process
- **RoHS/ELV Compliance History** = Always was RoHS compliant

Environmental:

- **Fluid Resistance** = Moisture, Splash Protection
- **Operating Temperature (°C)** = -55 - +110

Conditions for Usage:

- **Full Recovery Temperature (°C)** = 110
- **Shrink Temperature, Min. (°C)** = 80
- **High Temperature Compatible** = No

Operation/Application:

- **Application** = Cable Jacket Repair Sleeve, Cable Jacketing, Insulation and Protection, Sealing
- **Emission Free** = No
- **Product Use** = Cable Breakouts, Cable Ends, Connector-to-Cable Transitions, Electronic Components, Harnesses, Wire Breakouts, Wire Splices

Packaging Features:

- **Packaging Method** = Stick

Product Availability:

- **Product Source** = U.K., U.S.

Other:

- **Brand** = Raychem