



## TMS-SCE-1K-1/2-2.0-4 Product Details



**TMS-SCE-1K-1/2-2.0-4**

TE Internal Number: 8988010001

Active

### Heat Shrink Sleeve

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- TMS-SCE Series
- Military Grade
- Radiation Cross-Linked Polyolefin Material
- Shrink Ratio = 3:1
- Operating Temperature = -55 - 135 °C

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Wire and Harness ID Products</a> (PDF, English)</li> <li>• <a href="#">IDENTIFICATION PRINTER PRODUCT RIBBON MATRIX</a> (PDF, English)</li> <li>• <a href="#">TMS-SCE Military grade heat-shrinkable sleeves</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Series</a> = TMS-SCE</li> <li>• <a href="#">Grade</a> = Military</li> <li>• <a href="#">Color</a> = Yellow</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Recovered ID, Max.</a> (mm [in]) = 4.22 [0.166]</li> </ul> <p><b>Dimensions:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Expanded ID, Min.</a> (mm [in]) = 12.70 [0.500]</li> </ul> <p><b>Body Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Material</a> = Radiation Cross-Linked Polyolefin</li> <li>• <a href="#">Shrink Ratio</a> = 3:1</li> <li>• <a href="#">Sleeve Length, Nominal</a> (in [mm]) = 2 [50.8]</li> <li>• <a href="#">Recommended Wire OD Use Range</a> (mm [in]) = 4.64 - 10.79 [0.183 - 0.425]</li> <li>• <a href="#">Wall Thickness - Full Recovery (Nominal)</a> (mm [in]) = 0.61 [0.024]</li> </ul>	<p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not relevant for lead free process</li> <li>• <a href="#">RoHS/ELV Compliance History</a> = Always was RoHS compliant</li> </ul> <p><b>Environmental:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Operating Temperature (°C [°F])</a> = -55 - +135 [-67 - +275]</li> </ul> <p><b>Packaging Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Packaging Quantity</a> = 1,000</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Brand</a> = TE Connectivity</li> </ul>