

HDMI to VGA Active Adapter Video Converter with Audio (F/M)

MODEL NUMBER: P131-000-A-DISP



Active converter connects a VGA-enabled television or monitor to the HDMI port on your PC, MacBook, Chromebook, laptop or tablet.

Features

Now You Can Watch Video from Your HDMI Computer on a VGA Display This HDMI to VGA adapter helps you transmit video through your computer's HDMI port to a VGA-enabled television or monitor. It's an ideal tool for giving video presentations in conference rooms and classrooms, editing multiple documents on a larger screen, or streaming video for digital signage in crystal-clear 1080p. It also allows you to keep using your VGA display without the expense of replacing it.

Transmits Crystal-Clear 1080p Video and Stereo Audio To send high-definition video to a VGA television or monitor, connect the adapter directly to the display's VGA port, and connect an HDMI cable (sold separately) between the adapter's HDMI port and the source device. The adapter supports video resolutions up to 1920 x 1200 (including 1080p) at 60 Hz, as well as HDCP 1.4 and HDMI 1.4b compatibility. Connect the included audio cable between the adapter's audio port and the audio jack on your monitor, A/V receiver or speakers to receive stereo sound.

Ready to Use Right Out of the Package The molded one-piece unit is so compact that it fits in the palm of your hand, making it easy to carry in your backpack or laptop bag for quick connection anywhere. No software, drivers or external power supply is required. If additional power is needed, use the included USB cable to connect the adapter's USB Micro-B port to a USB charger or a USB-A port on the source device.

Highlights

- Recommended for video presentations or streaming 1080p video for digital signage
- Delivers HD picture quality at resolutions up to 1920 x 1200 (1080p) @ 60 Hz
- Included 3.5 mm audio cable carries stereo sound to monitor, receiver or speakers
- Molded one-piece converter fits easily in your backpack or laptop bag
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Play video from your HDMI computer on a large-screen VGA television
- Write and edit multiple documents on a bigger monitor
- Stream 1080p video for digital signage at a trade show
- Give a video presentation from your laptop at a meeting, training session or conference

System Requirements

- Source device with HDMI output
- Display device with VGA input

Package Includes

- P131-000-A-DISP HDMI to VGA Adapter with Audio (F/M)
- USB Micro-B to USB-A cable, 1 ft.
- 3.5 mm stereo audio cable, 1 ft.
- Quick Start Guide



Specifications

| OVERVIEW | |
|-----------------------------------|---|
| UPC Code | 037332231208 |
| INPUT | |
| Cable Length (ft.) | 0 |
| Cable Length (in.) | 0 |
| Bus Powered | Yes |
| Product Length (in.) | 2.46 |
| Product Length (ft.) | 0.20 |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | N/A |
| PHYSICAL | |
| Color | Black |
| Material of Construction | ABS |
| Rackmountable | No |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50 |
| Shipping Weight (kg) | 0.05 |
| Unit Dimensions (hwd / in.) | 1.33 x 2.46 x 0.37 |
| Unit Weight (kg) | 0.05 |
| Unit Weight (lbs.) | 0.10 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 104 F (0 to 40 C) |
| Storage Temperature Range | -4 to 140 F (-20 to 60 C) |
| Relative Humidity | 10% to 90% RH, Non-Condensing |
| Power Consumption (Watts) | 1.26 |
| CONNECTIONS | |
| Ports | 3 |
| Side A - Connector 1 | HD15 (MALE) |
| Side B - Connector 1 | 3.5MM (FEMALE); HDMI (FEMALE); MICRO-USB B (FEMALE) |
| Connector Plating | Nickel |



| | |
|--------------------------------------|---------------------------------|
| Contact Plating | Gold |
| FEATURES & SPECIFICATIONS | |
| Max Supported Video Resolution | 1920 x 1200 @ 60Hz |
| HDMI Specification | 1.4b |
| HDCP Specification | 1.4 |
| Audio Specification | 2 Channel Audio |
| Driver Required | No |
| Max Supported Color Depth | 8-bit |
| EDID Compatible | Yes |
| Technology | HDMI; Stereo Audio; VGA/SVGA |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to CE, FCC, REACH, RoHS2 |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>