

W-Series, Accessories
WQV 10/2**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

The versatile and extensive range of products - from 0.05 mm² to 300 mm² - means that you have diverse options for your applications at your disposal. Hardened steel for mechanical strength and high-quality tinned copper for optimum conductivity. All materials comply with RoHS requirements and have been tested to current environment guidelines.

General ordering data

| | |
|------------|--|
| Type | WQV 10/2 |
| Order No. | 1052560000 |
| Version | W-Series, Accessories, Cross-connector, For the terminals, No. of poles: 2 |
| GTIN (EAN) | 4008190154943 |
| Qty. | 50 pc(s). |

Data sheet

W-Series, Accessories WQV 10/2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------|---------|------------|---------|
| Length | 16.9 mm | Width | 7.55 mm |
| Height | 18 mm | Net weight | 3.6 g |

Temperatures

| | | | |
|----------------------------------|--------|----------------------------------|--------|
| Operating temperature | | Storage temperature | |
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |

Additional technical data

| | | | |
|--------------------------|-------------------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Version | For the terminals | | |

Rated data

| | |
|---------------|------|
| Rated current | 76 A |
|---------------|------|

Material data

| | | | |
|---------------------------|-------|--------|--------|
| Material | PA 66 | Colour | Yellow |
| UL 94 flammability rating | V-2 | | |

System specifications

| | |
|----------------|-----------------------|
| Product family | W-Series, Accessories |
|----------------|-----------------------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000489 | UNSPSC | 30-21-18-01 |
| eClass 5.1 | 27-14-11-40 | eClass 6.2 | 27-14-11-40 |
| eClass 7.1 | 27-14-11-40 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------|---|
| DXF | 08873_WQV_10-2_DXF.dxf |
| STEP | 1052560000_08873_WQV_10-2_STP.stp |