

Accessories

VGM25-SS68 11-20 BG

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Currently, heavy-duty connectors are used wherever there is a need for a secure, simple and time-saving assembly of machinery and facilities.

The connector housings are made of die-cast aluminium and offer excellent protection against dirt, moisture and mechanical stress.

Special modular connectors make it possible to integrate signals, power supply, pneumatics, and data connections into a single connector.

With the RockStar® heavy-duty connectors, Weidmüller offers a product line with many patented innovations that is oriented towards the future.

The RockStar® product line defines new standards with the comprehensive depth and width of its features. What other suppliers offer only as a custom configuration, Weidmüller supplies in its standard product line.

As a result, selecting the proper connector is now easier than ever. You save both time and money. And your work flow is optimised. Thus you can strengthen your position on the market and leverage your competitive advantage

General ordering data

Type	VGM25-SS68 11-20 BG
Order No.	1193570000
Version	Heavy Duty Connectors, Accessories, cable glands, Stainless steel
GTIN (EAN)	4032248976546
Qty.	50 pc(s).

Data sheet

Accessories
VGM25-SS68 11-20 BG

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	36.5 mm	Net weight	70 g
--------	---------	------------	------

Temperatures

Operating temperature	-40 °C...+130 °C
-----------------------	------------------

General data

AF size	30 mm	Cable diameter, max.	20 mm
Cable diameter, min.	11 mm	Cable gland	M 25
External thread	M 25	Length of thread	7.5 mm
Material	Stainless steel	O-Ring	Silicone
Protection degree	IP 68	Sealing material	TPE
Tightening torque, max.	10 Nm	Type of sealing	Rubber ring

Classifications

eClass 6.2	27-18-92-34	eClass 7.1	27-18-92-34
------------	-------------	------------	-------------

Approvals

Approvals



ROHS	Conform
------	---------