

## RF 180 GR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com



### Flexible - More flexible - Profilform

Modular housings in profile form - the flexible modular system comprising coloured and transparent plastic profiles and carrier modules

The combination of standard pitches mounted side by side in any arrangement and metre goods cut accurate to the millimetre creates the perfect balance between flexibility and economic efficiency:

- Pitch profiles with standard widths ranging from 5mm to 45mm allow the mounting of all standard PCB formats.
- Variable heights ensure maximum component density, even with larger electronics components.
- The different installation variations mean that mounting the enclosure directly is as easy as clipping components onto the terminal rail
- Solid hoods protect the module reliably from external influences

The recipe for success: variable profile + modular form components = flexible enclosure concept that offers a large surface area for the PCBs.

The modular concept is designed for modules with high space requirements and suitable for small component quantities and different widths.

### General ordering data

Order No.	<a href="#">1773400000</a>
Type	RF 180 GR
Version	Clip-in foot Grey, Clip-in foot, Width: 17.55 mm
GTIN (EAN)	4032248140602
Qty.	20 pc(s).

**RF 180 GR**

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com

**Technical data**

**Dimensions**

Length	79.2 mm	Width	17.55 mm
Height	26.55 mm		

**System characteristics**

Version	Clip-in foot	Cross-connection	No
Contact to terminal rail	No	Protection degree	IP 20
Encapsulation option	No		

**Material data**

Flammability class UL 94	V-2	Insulating material	PA 66
Colour	Grey	Continuous operating temp., min.	-25 °C
Continuous operating temp., max.	100 °C	Max. relative humidity during storage	93 %

**Classifications**

ETIM 3.0	EC001284	UNSPSC	30-21-18-01
eClass 6.0	27-14-92-14	eClass 7.0	27-14-92-14

**Approvals**

Approvals