



#### General ordering data

Order No.	1790010000
Part designation	HDC S6 12 BAS
Version	HDC insert, Female, 630 V, 48 A, Poles: 6 + 12 + PE, Axial screw connection, Size: 6
EAN	4032248212071
Qty	10 pc(s).

#### Product notes

Note, accessories	For axial screw connection ensure spanner size 2 AF. For other accessories see chapter G.
Note, ordering data	Please note: the signal contacts are designed for a rated voltage of 400V and a rated current of 16A.

#### Dimensions

Height socket C	47.15 mm
Total Length A	84.7 mm

**Dimensions****General data**

Colour	grey
Insulating material group	IIIa
Insulation material	PC glass fibre-reinforced (UL listed and approved for railway)
Insulation resistance	10 $\Omega$
No. of poles, total	6 + 12 + PE
Plugging cycles gold	$\geq 500$
Plugging cycles silver	$\geq 500$
Pollution severity	3
Temperature, max.	125 °C
Temperature, min.	-40 °C
UL 94 flammability class	V-0
Size	6
Series	MixMate
Type	Female
Designation	S6/12

**Connection data PE**

Type of PE connection	Screw connection
Rated cross-section	10 mm <sup>2</sup>
Max. connection cross-section, solid	0.5 mm <sup>2</sup>
Min. connection cross-section, solid	10 mm <sup>2</sup>
Min. connection cross-section, stranded	0.5 mm <sup>2</sup>
Max. connection cross-section, stranded	10 mm <sup>2</sup>
Min. connection cross-section "f" with wire end ferrule	0.5 mm <sup>2</sup>
Max. connection cross-section "f" with wire end ferrule	10 mm <sup>2</sup>
AWG, min.	AWG 14
AWG, max.	AWG 8
Fixing screw	M 5
Min. tightening torque	2 Nm
Blade size, crosshead	size PH2
Max. tightening torque	2.5 Nm
Blade size, slotted	1 x 5.5
Stripping length	8 mm

**Rating data**

Rated voltage (DIN EN 61984)	630 V
Rated current (DIN EN 61984)	48 A
Rated voltage to UL/CSA	600 V AC/DC
Rated impulse withstand voltage	8 kV

**Version**

Type of connection	Axial screw connection
Connection cross-section, min.	2.5 mm <sup>2</sup>
Connection cross-section, max.	10 mm <sup>2</sup>
AWG min.	AWG 14
AWG, max.	AWG 8

**Version**

Size	6
Surface	Silver, passivated
Volume resistance	≤ 4mΩ
Clamping screw	M 8 x 0,75 mm
Min. tightening torque	1.1 Nm
Max. tightening torque	1.7 Nm
Stripping length	8 mm
Material	copper alloy

**Approvals**

Approval body

**Classifications**

ETIM 2.0	EC001121
ETIM 3.0	EC001121
eClass 4.1	27-14-08-05
eClass 5.0	27-14-34-19
eClass 5.1	27-14-34-19

**Similar products**

Order No.	Part designation	Version
1789990000	HDC S4 SAS	HDC insert, Male, 1000 V, 65 A, Poles: 4 + PE, Axial screw connection, Size: 3
1789960000	HDC S4 0 SAS	HDC insert, Male, 830 V, 80 A, Poles: 4 + 0 + PE, Axial screw connection, Size: 6
1789980000	HDC S4 BAS	HDC insert, Female, 1000 V, 65 A, Poles: 4 + PE, Axial screw connection, Size: 3
1789970000	HDC S4 0 BAS	HDC insert, Female, 830 V, 80 A, Poles: 4 + 0 + PE, Axial screw connection, Size: 6
1790000000	HDC S6 12 SAS	HDC insert, Male, 690 V, 48 A, Poles: 6 + 12 + PE, Axial screw connection, Size: 6
1790020000	HDC S6 6 BAS	HDC insert, Female, 690 V, 100 A, Poles: 6 + 6 + PE, Axial screw connection, Size: 8
1790010000	HDC S6 12 BAS	HDC insert, Female, 630 V, 48 A, Poles: 6 + 12 + PE, Axial screw connection, Size: 6
1790030000	HDC S6 6 SAS	HDC insert, Male, 690 V, 100 A, Poles: 6 + 6 + PE, Axial screw connection, Size: 8