

MATERIAL:
 HOUSING MATERIAL: PBT
 COLOR: RED
 CONTACT MATERIAL: PHOSPHOR BRONZE
 CONTACT TYPE: STAMPED
 CONTACT PLATING: MATT TIN OVER NICKEL
 QUALITY CLASS: 25 MATING CYCLES
 PITCH: 2.54 MM PER ROW
 1.27 MM RIBBON CABLE

ENVIRONNEMENTAL:
 OPERATING TEMPERATURE: -40°C UP TO 105°C
 FLAMABILITY RATING: UL94-V0
 COMPLIANCE: LEAD FREE AND ROHS


ELECTRICAL:
 CURRENT RATING: 1.0 A PER PIN (CABLE)
 WORKING VOLTAGE: 100VAC
 INSULATION RESISTANCE: >1000MOHM
 DIELECTRIC WITHSTANDING VOLT.: 500VAC/MN
 CONTACT RESISTANCE: 10mOHM MAX

DIMENSION:
 DIM.A= 1.27 x No. of Spaces
 DIM.B= DIM.A + 3.3
 DIM.C= DIM.A + 2.1
 DIM.D= DIM.A + 4.7

AVAILABLE
 xx : 4 TO 26 CIRCUITS

PACKAGING:
 x = 2 TUBE
 x = 7 TAPE & REEL

RoHS Compliant			
G			
F			
E			
D			
C			
B	27-NOV-07	MODIFICATIONS	EC
A	03-NOV-06	PDF	JP
REV	DATE	FILE	BY

PROJECTION:

 APPROVAL: RJ

GENERAL TOLERANCE
 .X = +/- 0.2
 .XX = +/- 0.15
 UNIT: MM
 SCALE:
 SHEET: 1/1
 DRAW: EAGER



DESCRIPTION: MM MALE IDC CONNECTOR
 WERI PART NO: 69015700 xx 7 x
 DRAWING NO: 69015700

SIZE
A4

A
 B
 C
 D