



## 1200V SiC MOSFET Power Module

$V_{DS}$	1200 V
$R_{DS,on}$	18 m $\Omega$
$I_D (T_C=25^\circ\text{C})$	113 A
$T_{J,max}$	175 $^\circ\text{C}$

### Features

- High speed switching SiC MOSFETs
- Simple to drive
- Kelvin reference for stable operation


### Benefits

- Low switching losses
- Low junction to case thermal resistance
- Very rugged and easy mount
- Direct mounting to heatsink (isolated package)

### Applications

- Photovoltaic Inverter
- Battery charger
- Server power supplies
- Energy storage system

### Package



- (1)  $S_G$  (Driver Source)  
 (2) G (Gate)  
 (3) D (Drain)  
 (4) S (Source)

Part #	Package	Marking
GCMX020B120S1-E1	SOT-227	GCMX020B120S1-E1



### Absolute Maximum Ratings

Characteristics	Symbol	Conditions	Values	Unit
Drain-Source Voltage	$V_{rated}$	$V_{GS}=0V, I_D=1\mu A$	1200	V
Continuous Drain Current	$I_{DS}$	$T_C=25^\circ\text{C}, V_{GS}=20V$	113	A
		$T_C=100^\circ\text{C}, V_{GS}=20V$	81	
Body Diode Drain Current	$I_{SD}$	$T_C=25^\circ\text{C}, V_{GS}=-5V$	97	
Pulsed Drain Current	$I_{DS,pulse}^*$	$T_C=25^\circ\text{C}, V_{GS}=20V$	250	
Gate Source Voltage	$V_{GSmax}$		-10/25	V
	$V_{GSop}$	Recommended operational	-5/20	
Power Dissipation	$P_{tot}$	$T_C=25^\circ\text{C}$	395	W
Operating & Storage Temperature	$T_J, T_{storage}$	Continuous	-55...175	$^\circ\text{C}$

\*Pulse width is limited by  $T_{J,max}$

# 1200V SiC MOSFET Power Module

# GCMX020B120S1-E1

Static Electrical Characteristics, at  $T_J=25^\circ\text{C}$ , unless otherwise specified

Characteristics	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=1mA$	1200	-	-	V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=1200V, V_{GS}=0V$	-	0.1	1	$\mu A$
		$V_{DS}=1200V, V_{GS}=0V, T_J=175^\circ\text{C}$	-	1	-	
Gate-Source Leakage Current	$I_{GSS+}$	$V_{GS}=20V, V_{DS}=0V$	-	10	1000	nA
	$I_{GSS-}$	$V_{GS}=-5V, V_{DS}=0V$	-	-10	-1000	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}, I_D=20mA$	1.8	2.8	4	V
		$V_{GS}=V_{DS}, I_D=20mA, T_J=175^\circ\text{C}$	-	1.7	-	
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=20V, I_D=50A$	-	18.1	28	m $\Omega$
		$V_{GS}=20V, I_D=25A$	-	17.6	26	
		$V_{GS}=20V, I_D=50A, T_J=125^\circ\text{C}$	-	24	-	
		$V_{GS}=20V, I_D=50A, T_J=175^\circ\text{C}$	-	30	-	
Transconductance	$g_{fs}$	$V_{DS}=20V, I_D=50A$	-	25	-	S
Internal Gate Resistance	$R_{G(int)}$	f=1MHz, $V_{AC}=25mV$ , D-S Short	-	0.8	-	$\Omega$

AC Electrical Characteristics, at  $T_J=25^\circ\text{C}$ , unless otherwise specified

Characteristics	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Input Capacitance	$C_{ISS}$	$V_{GS}=0V$	-	5349	-	pF
Output Capacitance	$C_{OSS}$	$V_{DS}=1000V$	-	273	-	
Reverse Transfer Capacitance	$C_{RSS}$	f=200kHz	-	19	-	
Coss Stored Energy	$E_{OSS}^*$	$V_{AC}=25mV$	-	161	-	$\mu J$
Turn-On Switching Energy	$E_{ON}$	$V_{DD}=800V, I_{DS}=50A,$ $R_{G(ext)}=3.9\Omega,$	-	0.67	-	mJ
Turn-Off Switching Energy	$E_{OFF}$			-	0.18	
Turn-On Delay Time	$t_{D(on)}$	$V_{GS}=-5/+20V, L=273\mu H,$ FWD= GCMX020B120S1-E1	-	21	-	ns
Rise Time	$t_R$		-	8	-	
Turn-Off Delay Time	$t_{D(off)}$		-	42	-	
Fall Time	$t_F$		-	18	-	
Total Gate Charge	$Q_G$		$V_{DD}=800V, I_{DS}=50A$	-	216	
Gate to Source Charge	$Q_{GS}$	$V_{GS}=-5/20V$	-	76	-	
Gate to Drain Charge	$Q_{GD}$		-	45	-	

\* $E_{OSS}$  is calculated from  $C_{OSS}$  curve

Body Diode Characteristics, at  $T_J=25^\circ\text{C}$ , unless otherwise specified

Characteristics	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Diode Forward Voltage	$V_{SD}$	$V_{GS}=-5V, I_S=25A$	-	3.7	-	V
Reverse Recovery Time	$t_{RR}$	$I_S=50A, V_R=800V, V_{GS}=-5V$ di/dt=7.5A/ns	-	17	-	ns
Reverse Recovery Charge	$Q_{RR}$		-	587	-	nC
Peak Reverse Recovery Current	$I_{RRM}$		-	59	-	A
Reverse Recovery Energy	$E_{RR}$		-	0.20	-	mJ

Thermal and Package Characteristics, at  $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified

Characteristics	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal resistance, junction-case	$R_{thJC}$		-	0.31	0.38	$^\circ\text{C/W}$
Mounting torque	$M_d$	M4-0.7 screws	1.1	-	1.5	N-m
Terminal connection torque	$M_{dt}$	M4-0.7 screws	-	1.1	1.3	
Package weight	$W_t$		-	32	-	g
Isolation voltage	$V_{ISOL}$	$I_{ISOL} < 1\text{ mA}$ , 50/60 Hz, 2 s	4000	-	-	V

## Typical Performance




Figure 1. Output Characteristics  $T_j = -55^\circ\text{C}$




Figure 2. Output Characteristics  $T_j = 25^\circ\text{C}$

# 1200V SiC MOSFET Power Module

# GCMX020B120S1-E1




Figure 3. Output Characteristics  $T_J = 125^\circ\text{C}$




Figure 4. Output Characteristics  $T_J = 175^\circ\text{C}$




Figure 5. Normalized On-Resistance vs. Temperature




Figure 6. On-Resistance vs. Drain Current For Various Temperature




Figure 7. On-Resistance vs. Temperature For Various Gate Voltages




Figure 8. Transfer Characteristic for Various Junction Temperatures




Figure 9. Body Diode Characteristics at  $T_J = -55^\circ\text{C}$




Figure 10. Body Diode Characteristics at  $T_J = 25^\circ\text{C}$




Figure 11. Body Diode Characteristics at  $T_J = 125^\circ\text{C}$




Figure 12. Body Diode Characteristics at  $T_J = 175^\circ\text{C}$




Figure 13. Threshold Voltage vs. Temperature




Figure 14. Gate Charge Characteristics

# 1200V SiC MOSFET Power Module

# GCMX020B120S1-E1




Figure 15. Output Capacitor Stored Energy




Figure 16. Capacitance vs Drain-Source Voltage




Figure 17. Continuous Drain Current Derating vs. Case Temperature




Figure 18. Maximum Power Dissipation Derating vs Case Temperature




Figure 19. Transient Thermal impedance (Junction to Case)




Figure 20. Safe Operating Area




Figure 21. Clamped Inductive Switching Energy vs. Drain Current




Figure 22. Clamped Inductive Switching Energy vs.  $R_{G(ext)}$



# 1200V SiC MOSFET Power Module

# GCMX020B120S1-E1




Figure 23. Clamped Inductive Switching Energy vs. Temperature




Figure 24. Switching Times vs  $R_{G(ext)}$




Figure 25. Switching Times vs. Drain Current




Figure 26.  $dv/dt$  and  $di/dt$  vs. Drain Current

# 1200V SiC MOSFET Power Module

# GCMX020B120S1-E1




Figure 27. dv/dt and di/dt vs.  $R_{G(ext)}$




Figure 28. Turn-off Transient Definitions




Figure 30. Turn-on Transient Definitions





Figure 31. Reverse Recovery Definitions

# 1200V SiC MOSFET Power Module

**GCMX020B120S1-E1**

## Package Dimensions SOT-227



Sym	Millimeters		Inches	
	Min	Max	Min	Max
A	31.67	31.90	1.247	1.256
B	7.95	8.18	0.313	0.322
C	4.14	4.24	0.163	0.167
D	4.14	4.24	0.163	0.167
E	4.14	4.24	0.163	0.167
F	14.94	15.09	0.588	0.594
G	30.15	30.25	1.187	1.191
H	38.00	38.10	1.496	1.500
I	4.75	4.83	0.187	0.190
J	11.68	12.19	0.460	0.480
K	9.45	9.60	0.372	0.378
L	0.76	0.84	0.030	0.033
M	12.62	12.88	0.497	0.507
N	25.15	25.30	0.990	0.996
O	24.79	25.04	0.976	0.986
P	3.02	3.15	0.119	0.124
Q	6.71	6.96	0.264	0.274
R	4.17	4.42	0.164	0.174
S	2.08	2.13	0.082	0.084
T	3.28	3.63	0.129	0.143
U	26.75	26.90	1.053	1.059
V	3.86	4.24	0.152	0.167
W	20.55	26.90	0.809	0.814
X	5.45	5.85	0.215	0.230
Y	3.15	3.66	0.124	0.144
Z	0.00	0.13	0.000	0.005

# 1200V SiC MOSFET Power Module

**GCMX020B120S1-E1**

Revision History		
Date	Revision	Notes
12/6/2021	0.1	Preliminary release
9/28/2022	0.2	Updated switching test data
8/4/2023	1.0	Initial release

## Notes

### RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented March, 2013. RoHS Declarations for this product can be obtained from the Product Documentation sections of [www.SemiQ.com](http://www.SemiQ.com).

### REACH Compliance

REACH substances of high concern (SVHC) information is available for this product. Since the European Chemicals Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact our office at SemiQ Headquarters in Lake Forest, California to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

SemiQ Inc., reserves the right to make changes to the product specifications and data in this document without notice. SemiQ products are sold pursuant to SemiQ's terms and conditions of sale in place at the time of order acknowledgement.

This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control.

SemiQ makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SemiQ assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using SemiQ products.

To obtain additional technical information or to place an order for this product, please contact us. The information in this datasheet is provided by SemiQ. SemiQ reserves the right to make changes, corrections, modifications, and improvements of datasheet without notice.