



MiniSKiiP® DUAL 2

1200 V / 150 A

Topology features

- Half Bridge
- Temperature sensor

Component features

- Easy paralleling
- Low turn-off losses
- Low collector emitter saturation voltage
- Positive temperature coefficient
- Short tail current
- Switching optimized for EMC

Housing features

- Base isolation: Al₂O₃
- Easy assembly in one mounting step
- Flexible PCB design w/o pin holes
- Half-Bridge configuration
- Rugged solderless spring contacts


Target applications

- Industrial Drives
- Power Supply


Types

- 80-M2122PA150M7-K708F70

MiniSKiiP® 2 16 mm housing



Schematic



**Maximum Ratings** $T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Half-Bridge Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	180	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	300	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	376	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

Half-Bridge Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	132	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	300	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	233	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties**Thermal Properties**

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	5500	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance		With std lid For more informations see handling instructions	6,3	mm
Clearance		With std lid For more informations see handling instructions	6,3	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Half-Bridge Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$		10	0,015	25	5,4	6	6,6	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	15		150	25 125 150		1,63 1,81 1,86	1,9 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}	0	1200		25			200	μA
Gate-emitter leakage current	I_{GES}	20	0		25			1000	nA
Internal gate resistance	r_g						2		Ω
Input capacitance	C_{ies}						32000		pF
Output capacitance	C_{oes}	0	10		25		960		pF
Reverse transfer capacitance	C_{res}						380		pF
Gate charge	Q_g	$V_{CC} = 600$ V	0/15		150	25		1140	nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)					0,25		K/W
--	---------------	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$					25 125 150		372 379 383	ns
Rise time	t_r	$R_{gon} = 4$ Ω $R_{goff} = 4$ Ω				25 125 150		57 66 72	ns
Turn-off delay time	$t_{d(off)}$		±15	600	150	25 125 150		295 325 333	ns
Fall time	t_f					25 125 150		91,26 101,64 112,65	ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 14,66$ μC $Q_{tFWD} = 23,87$ μC $Q_{tFWD} = 25,49$ μC				25 125 150		17,88 22,69 23,61	mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		9,73 12,47 13,79	mWs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		
Half-Bridge Diode										
Static										
Forward voltage	V_F			150	25 125 150		1,74 1,83 1,84	2,15 ⁽¹⁾		V
Reverse leakage current	I_R	$V_T = 1200$ V			25			110		μA
Thermal										
Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)					0,41			K/W
Dynamic										
Peak recovery current	I_{RRM}				25 125 150		88,3 93,99 96,44			A
Reverse recovery time	t_{rr}				25 125 150		356,72 522,07 561,16			ns
Recovered charge	Q_r	$di/dt=2429$ A/μs $di/dt=2186$ A/μs $di/dt=2148$ A/μs	±15	600	150	25 125 150	14,66 23,87 25,49			μC
Reverse recovered energy	E_{rec}				25 125 150		4,76 8,52 9,1			mWs
Peak rate of fall of recovery current	$(di_r/dt)_{max}$				25 125 150		321,65 321,92 319,54			A/μs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	V_{CE} [V]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		5		kΩ
Deviation of R_{100}	$A_{R/R}$	$R_{100} = 493 \Omega$				100	-5		5	%
Power dissipation	P							245		mW
Power dissipation constant	d					25		1,4		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 2 \%$						3375		K
B-value	$B_{(25/100)}$	Tol. $\pm 2 \%$						3437		K
Vincotech Thermistor Reference									K	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Half-Bridge Switch Characteristics

figure 1. IGBT

Typical output characteristics
 $I_C = f(V_{CE})$




figure 2. IGBT

Typical output characteristics
 $I_C = f(V_{CE})$




figure 3. IGBT

Typical transfer characteristics
 $I_C = f(V_{GE})$





figure 4. IGBT

Transient thermal impedance as a function of pulse width
 $Z_{th(j-s)} = f(t_p)$



IGBT thermal model values


R (K/W)	τ (s)
5,78E-02	1,92E+00
1,16E-01	2,60E-01
5,63E-02	8,69E-02
1,65E-02	1,02E-02
6,13E-03	8,05E-04



Half-Bridge Switch Characteristics

figure 5. IGBT


Safe operating area
 $I_C = f(V_{CE})$



$D =$ single pulse
 $T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$

figure 6. IGBT

Gate voltage vs gate charge
 $V_{GE} = f(Q_g)$



$I_C = 75 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$



Half-Bridge Diode Characteristics

figure 7. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,407$ K/W
 FWD thermal model values

R (K/W)	τ (s)
2,97E-02	3,00E+00
6,83E-02	5,66E-01
1,89E-01	8,32E-02
8,43E-02	1,56E-02
3,62E-02	1,11E-03




Thermistor Characteristics

figure 9. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$






Half-Bridge Switching Characteristics

figure 10. IGBT

Typical switching energy losses as a function of collector current
 $E = f(I_c)$




With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

T_f : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 11. IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor
 $E = f(R_g)$




With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 150$ A

T_f : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 12. FWD

Typical reverse recovered energy loss as a function of collector current
 $E_{rec} = f(I_c)$




With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω

T_f : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 13. FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor
 $E_{rec} = f(R_g)$



With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 150$ A


T_f : 25 °C (blue), 125 °C (black), 150 °C (red)



Half-Bridge Switching Characteristics

figure 14. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$

figure 15. IGBT


Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 150 \text{ A}$

figure 16. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $T_j:$ — 25 °C
— 125 °C
— 150 °C

figure 17. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 150 \text{ A}$
 $T_j:$ — 25 °C
— 125 °C
— 150 °C




Half-Bridge Switching Characteristics

figure 18. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \ \Omega$

T_j : — 25 °C
— 125 °C
— 150 °C

figure 19. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 150 \text{ A}$

T_j : — 25 °C
— 125 °C
— 150 °C

figure 20. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \ \Omega$

T_j : — 25 °C
— 125 °C
— 150 °C

figure 21. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 150 \text{ A}$


T_j : — 25 °C
— 125 °C
— 150 °C



Half-Bridge Switching Characteristics

figure 22. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_c)$




With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C
$R_{gon} = 4$ Ω	$T_j = 150$ °C

figure 23. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{gon})$




With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C
$I_c = 150$ A	$T_j = 150$ °C

figure 24. IGBT

Reverse bias safe operating area
 $I_c = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω



Half-Bridge Switching Definitions

figure 25. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 26. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 27. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 28. IGBT

Turn-on Switching Waveforms & definition of t_r





Half-Bridge Switching Definitions


figure 29. FWD

Turn-off Switching Waveforms & definition of t_{rr}



figure 30. FWD


Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)






Vincotech

Ordering Code	
Version	Ordering Code
With std lid (6.5mm height) + no thermal grease	80-M2122PA150M7-K708F70-/0A/
With thin lid (2.8mm height) + no thermal grease	80-M2122PA150M7-K708F70-/0B/
With std lid (6.5mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M2122PA150M7-K708F70-/1A/
With thin lid (2.8mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M2122PA150M7-K708F70-/1B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M2122PA150M7-K708F70-/4A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M2122PA150M7-K708F70-/4B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M2122PA150M7-K708F70-/5A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M2122PA150M7-K708F70-/5B/

Marking						
Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTTTVV		WWYY	UL VIN	LLLLL
Datamatrix		Type&Ver	Lot number	Serial	Date code	
	TTTTTTTV	LLLLL	SSSS	WWYY		


Outline				
Pin table [mm]				Function
Pin	X	Y		
1	-7,6	21,9		S12
2	4,7	21,9		G12
3	18,6	21,8		DC+
4	18,6	18,6		DC+
5	18,6	15,4		DC+
6	18,6	12,2		DC+
7	18,6	9		DC+
8	22,5	21,8		DC+
9	22,5	18,6		DC+
10	22,5	15,4		DC+
11	22,5	12,2		DC+
12	22,5	9		DC+
13	-22,5	7,8		Ph
14	-22,5	4,6		Ph
15	-22,5	1,4		Ph
16	-22,5	-1,8		Ph
17	-22,5	-5		Ph
18	-18,6	7,8		Ph
19	-18,6	4,6		Ph
20	-18,6	1,4		Ph
21	-18,6	-1,8		Ph
22	-18,6	-5		Ph
23	-6,8	1,6		Therm1
24	-6,8	-1,6		Therm2
25	18,6	-9		DC-
26	18,6	-12,2		DC-
27	18,6	-15,4		DC-
28	18,6	-18,6		DC-
29	18,6	-21,8		DC-
30	22,5	-9		DC-
31	22,5	-12,2		DC-
32	22,5	-15,4		DC-
33	22,5	-18,6		DC-
34	22,5	-21,8		DC-
35	4,6	-18,7		S11
36	1,7	-21,9		G11



Pad positions refers to center point. For more informations on pad design please see package data



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12	IGBT	1200 V	150 A	Half-Bridge Switch	
D11, D12	FWD	1200 V	150 A	Half-Bridge Diode	
Rt	NTC			Thermistor	




Packaging instruction				
Standard packaging quantity (SPQ) 72	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for MiniSKiiP® 2 packages see vincotech.com website.

Package data
Package data for MiniSKiiP® 2 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
80-M2122PA150M7-K708F70-D2-14	1 May. 2022	New Datasheet format, module is unchanged Correct tau values of thermal characteristic	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.