


REV.	DESCRIPTION	DRAWN	DATE
1	INITIAL RELEASE	FROS	2021/03/23



DATE CODE: YYWWD
 YY: YEAR
 WW: WEEK (01~52)
 D: DAY (1~7)




SPECIFICATION:

1. ELECTRICAL
 - 1.1 Current Rating: 0.6A per pin
 - 1.2 Voltage Rating: 25V AC
 - 1.3 Contact Resistance: 60mΩ max.
 - 1.4 Insulation Resistance: 100MΩ
 - 1.5 Dielectric Withstanding Voltage: 500VAC

2. MECHANICAL
 - 2.1 Durability: 50 Cycle
 - 2.2 Insertion Force: 59.8N max.
 - 2.3 Extraction Force: 44.6N max.

3. ENVIRONMENTAL
 - 3.1 Operating temperature range: -40°C~+85°C
 - 3.2 Storage temperature range: -40°C~+85°C

4. SOLDER ABILITY
 - 4.1 Recommended IR-Reflow Temperature: 260°C





4	PEG	Stainless steel, 50u"~150u" matte tin plating over 50u"~150u" nickel plating
3	LATCH	Stainless steel
2	CONTACT	Copper alloy, 1u" gold plating on contact and solder area, under plating nickel
1	HOUSING	Thermoplastic, UL94V-0, Black

NO.		PART NAME		DESCRIPTION	
UNLESS OTHERWISE SPECIFIED TOLERANCE					
UNIT:	DECIMAL	LINEAR	ANGLES		
mm	X.	±0.50	±5°		
	X.X	±0.25	±3°		
	X.XX	±0.12	±1°		
www.attend.com.tw					
DRAWN	Fros	2021/03/23	DRAWN NAME:		
CHECKED	Tim	2021/03/23	DDR5 SODIMM Socket, Horizontal 8.0H, RVS, G/F, Black, Reel, Solder PEG		
APPROVED	Ken	2021/03/23	PRODUCT NO.	126A-80A10	
SCALE 1:25		SHEET 1/2	SIZE A4	FILE NAME	126A-80A10_B_1




REV.	DESCRIPTION	DRAWN	DATE
	see sheet one		



RECOMMEND P.C.BOARD LAYOUT
 PCB THICKNESS 0.80mm MIN.
 PCB LAYOUT GENERIC TOLERANCE:±0.05
 ([Z-] :PCB SURFACE)

DETAIL H
 SCALE 1:1






MATING: ① INSERTING → ② ROTATING → ③ FIXED
 UNMATING: ④ UNFIXED → ⑤ RISE UP → ⑥ EXTRACTING

MATING/UNMATING VIEW


UNLESS OTHERWISE SPECIFIED TOLERANCE				
UNIT:	DECIMAL	LINEAR	ANGLES	
mm	X.	±0.50	±5°	
	X.X	±0.25	±3°	
	X.XX	±0.12	±1°	
DRAWN	Fros	2021/03/23	DRAWN NAME: DDR5 SODIMM Socket, Horizontal 8.0H, RVS, G/F, Black, Reel, Solder PEG	
CHECKED	Tim	2021/03/23		
APPROVED	Ken	2021/03/23		
SCALE	1.25	SHEET 2/2	SIZE A4	PRODUCT NO. 126A-80A10
FILE NAME 126A-80A10_B_1				





REV.	DESCRIPTION	DRAWN	DATE
1	INITIAL RELEASE	FROS	2021/03/23




DETAIL E
SCALE 2:1



DETAIL D
SCALE 2:1





DETAIL G
SCALE 2:1






DETAIL F
SCALE 2:1

RECOMMEND MODULE CONFIGURATION

UNLESS OTHERWISE SPECIFIED TOLERANCE				 www.attend.com.tw	
UNIT:	DECIMAL	LINEAR	ANGLES		
mm	X.	±0.50	±5°		
	X.X	±0.25	±3°		
	X.XX	±0.12	±1°		
DRAWN	Fros	2021/03/23	DRAWN NAME:		
CHECKED	Tim	2021/03/23	262 PIN DDR5 SODIMM, 0.5MM PITCH PACKAGE		
APPROVED	Ken	2021/03/23	PRODUCT NO.		
	SCALE	SHEET	SIZE	FILE NAME	
	1.25	1/1	A4	126A-CARD_B_1	

REV.	DESCRIPTION	DRAWN	DATE
1	INITIAL RELEASE	FROS	2021/03/23



PART NO.	PCS/REEL	REEL/CARTON	PCS/CARTON
126A-80A00	300	3	900
126A-80A10	300	3	900

UNLESS OTHERWISE SPECIFIED TOLERANCE

UNIT:	DECIMAL	LINEAR	ANGLES
mm	X.	±0.50	±5°
	X.X	±0.25	±3°
	X.XX	±0.12	±1°



www.attend.com.tw

DRAWN	Fros	2021/03/23	DRAWN NAME: Packaging for DDR5 SODIMM Socket, Horizontal, 8.0H, Reel 88.0mm
CHECKED	Tim	2021/03/23	
APPROVED	Ken	2021/03/23	
			PRODUCT NO. SEE TABLE
SCALE	N/A	SHEET 1/1	SIZE A4
FILE NAME		126A-80AX0_D_1	