



ITEM	DESC.	MATERIAL	REMARKS
5	OUT SHELL	STEEL	OVER-PLATING: Ni 80~200u"
4	PLASTIC PARTS	LCP UL94V-0	30% G/F ,Blue
3	SHELL	STAINLESS STEEL 201	OVER-PLATING: Ni 40u"
2	4P TERMINAL	PHOSPHOR BRONZE C5191	CONTACT AREA: 30u" SOLDER AREA: Sn 80u"
1	5P TERMINAL	BRASS C2680	UNDER-PLATING: Ni 50u"

Limited supply by further check with us. ↓

Pin Assignments	
Pin No.	Signal Name
1	VBUS
2	D-
3	D+
4	GND
5	StdA_SSRX-
6	StdA_SSRX+
7	GND_DRAIN
8	StdA_SSTX-
9	StdA_SSTX+
Shell	Shield

Product Number	Description
209B-SG01	USB3.0 A Receptacle, SMT Type ,Contact:30u" Gold Plating

UNLESS OTHERWISE SPECIFIED TOLERANCE		
ANGLES	ANG.	±5°
LINEAR	0.	±0.3
	0.0	±0.25
	0.00	±0.20
SCALE	AS SHOWN	UNIT: mm
DRAWN	Willis	2014/07/18
CHECKED	Angel	2014/07/18
APPROVED	Ken	2014/07/18



ATTEND

www.attend.com.tw

DRAWN NAME: USB 3.0 A Receptacle SMT Type

PRODUCT NO. 209B-SG01

- △ Revise:
- △ Revise:
- △ Revise:

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME
1			4			A4	1.0	209B-SG01_B_4.1